

# THE ORKNEY FISHING BOAT RANGE

## Specialised Workboats

Most of our hulls provide an ideal basis for specialised workboats. We can, for example, fit extra reinforcement and heavy duty fendering and on the larger boats install dual steering, gantries and pot haulers. A wide variety of engine installations is available including water jet drives. If you are looking for a boat to work from we would be happy to discuss your requirements.



DISPLACEMENT

PERFORMANCE

DAY ANGLER

Model	Length	Beam	Weight	Foam Buoyancy Self Bailing	Performance Indicator	Recommended Engine			Max. HP	Design Speed	
						TYPE	HP RANGE	SHAFT LENGTH		MAXIMUM	OPTIMUM
NOTES	1			2		3			4		5
<b>ANGLER 11</b>	10'8" 3.25 M	4'11" 1.5 M	160 LBS 73KG	STANDARD N/A	2HP - 2.4KNOTS 4HP - 5.5KNOTS 6HP - 6.0KNOTS	S0	2-4	S	6	6KNOTS	5 KNOTS
<b>SPINNER 13</b>	13'0" 3.96 M	5'5" 1.65 M	250 LBS 114 KG	STANDARD N/A	4HP - 5KNOTS 6HP - 6.5KNOTS 8HP - 7.5KNOTS	S0	4-6	L	8	8KNOTS	6KNOTS
<b>LONGLINER 16</b>	16'0" 4.88 M	5'7" 1.70 M	400 LBS 182 KG	STANDARD N/A	5HP - 5 KNOTS 10HP - 7.5KNOTS 15HP - 8.5KNOTS	S0	5-10	L	15	10 KNOTS	7KNOTS
<b>FOUR 40</b>	14'4" 4.37 M	5'8" 1.73 M	440 LBS 200 KG	STANDARD N/A	10HP - 8.5KNOTS 15HP - 17 KNOTS 20HP - 22 KNOTS	S0	5-15	L	20	22KNOTS	14KNOTS
<b>FIVE 20</b>	16'11" 5.17 M	6'1" 1.86 M	750LBS 340 KG	STANDARD UNDER WAY	15HP - 10KNOTS 25HP - 20KNOTS 35HP - 24KNOTS	S0	10-30	L	35	22KNOTS	14KNOTS
<b>FIVE 90T</b>	19'3" 5.87 M	6'10" 2.08 M	1300 LBS 590 KG	STANDARD STANDARD	20HP - 10KNOTS 40HP - 19KNOTS 60HP - 23KNOTS	S0 T0	20-50 2x30	L L	60 70	22KNOTS	15KNOTS
<b>FIVE 90TS</b>	19'3" 5.87 M	6'10" 2.08 M	1350 LBS 614 KG	STANDARD STANDARD	20HP - 10KNOTS 40HP - 19KNOTS 60HP - 23KNOTS	S0 T0	20-50 2x30	L L	60 70	22KNOTS	15KNOTS
<b>DAY ANGLER 19+</b>	19'6" 5.95 M	7'6" 2.29 M	1650 LBS 750 KG	OPTIONAL STANDARD	30HP - 12KNOTS 50HP - 18KNOTS 65HP - 23KNOTS	S0 T0 SZ	30-60 2x35 50-80	L L L	65 75 105	23KNOTS	15KNOTS
<b>COMMERCIAL 21</b>	21'0" 6.40 M	7'8" 2.32 M	1500 LBS 700 KG	OPTIONAL STANDARD	30HP - 12KNOTS 65HP - 22KNOTS 80HP - 23KNOTS	S0 T0 SZ	30-65 2x40 50-110	L L L	80 100 125	23KNOTS	15KNOTS
<b>DAY ANGLER 21</b>	21'0" 6.40 M	7'8" 2.32 M	1870 LBS 850 KG	OPTIONAL STANDARD	30HP - 11 KNOTS 65HP - 20KNOTS 80HP - 23KNOTS	S0 T0 SZ	30-65 2x40 50-110	L L L	80 100 125	23KNOTS	15KNOTS
<b>COMMERCIAL 23</b>	23'0" 7.00 M	8'1" 2.50 M	1980 LBS 900 KG	OPTIONAL STANDARD	40HP - 12KNOTS 90HP - 22KNOTS 115HP - 24KNOTS	S0 T0 SZ	40-90 2x50 50-130	L L L	115 120 150	24KNOTS	16KNOTS
<b>DAY ANGLER 23</b>	23'0" 7.00 M	8'1" 2.50 M	2310 LBS 1050 KG	OPTIONAL STANDARD	40HP - 12KNOTS 90HP - 22KNOTS 115HP - 24KNOTS	S0 T0 SZ	40-90 2x50 50-130	L L L	115 120 150	24KNOTS	16KNOTS

Notes 1. Weight of basic boat only. 2. Performance indicator based on one crew plus gear but otherwise light displacement. 3. S0=Single outboard engine T0=Twin outboard engines SZ=Single sterndrive 4. Tiller steer versions of performance and Day Angler models have reduced horse power ratings (consult your dealer or owners handbook) 5. Max speed in smooth water with light load. Boats should not be driven above the maximum design speed particularly in rough conditions.

Please note that performance indicators, where given, are approximate and not guaranteed. Lengths quoted do not include engines and other dimensions and data is for general guidance. Please ask your dealer for advice regarding suitability for your application particularly if it is unusual or arduous.



Orkney Boats Ltd, Ford Lane Industrial Estate,  
Ford Lane, Yapton, Arundel, West Sussex BN18 0DF  
Telephone: 01243 551456 Fax: 01243 551914

We are constantly seeking ways to improve our products and we therefore reserve the right to change specifications as necessary.  
Some illustration in this leaflet show boats fitted with optional equipment.  
For full details of accessories, please see current price list.  
Terms of business are available on request. E & OE