

Orkney

BOATS



BOATS

FISHING



MORE THAN JUST BOATS TO FISH FROM

ORKNEY

THE ORKNEY FISHING BOAT RANGE

Specialised Workboats

Most of our hulls provide an ideal basis for specialised workboats. We can, for example, fit extra reinforcement and heavy duty fendering and on the larger boats install dual steering, ganties and pot haulers. A wide variety of engine installations is available including water jet drives. If you are looking for a boat to work from we would be happy to discuss your requirements.



DISPLACEMENT

PERFORMANCE

DAY ANGLER

Model	Length	Beam	Weight	Foam Buoyancy Self Bailing	Performance Indicator	Recommended Engine			Max. HP	Design Speed	
						TYPE	HP RANGE	SHAFT LENGTH		MAXIMUM	OPTIONUM
NOTES	1			2		3			4		5
ANGLER 11	10'8" 3.25 M	4'11" 1.5 M	160 LBS 73KG	STANDARD N/A	2HP - 2.4KNOTS 4HP - 5.5KNOTS 6HP - 6.0KNOTS	SO	2-4	S	6	6KNOTS	5 KNOTS
SPINNER 13	13'0" 3.96 M	5'5" 1.65 M	250 LBS 114 KG	STANDARD N/A	4HP - 5KNOTS 6HP - 6.5KNOTS 8HP - 7.5KNOTS	SO	4-6	L	8	8KNOTS	6KNOTS
LONGLINER 16	16'0" 4.88 M	5'7" 1.70 M	400 LBS 182 KG	STANDARD N/A	5HP - 5 KNOTS 10HP - 7.5KNOTS 15HP - 8.5KNOTS	SO	5-10	L	15	10 KNOTS	7KNOTS
FOUR 40	14'4" 4.37 M	5'8" 1.73 M	440 LBS 200 KG	STANDARD N/A	10HP - 8.5KNOTS 15HP - 17 KNOTS 20HP - 22 KNOTS	SO	5-15	L	20	22KNOTS	14KNOTS
FIVE 20	16'11" 5.17 M	6'1" 1.86 M	750LBS 340 KG	STANDARD UNDER WAY	15HP - 10KNOTS 25HP - 20KNOTS 35HP - 24KNOTS	SO	10-30	L	35	22KNOTS	14KNOTS
FIVE 90^T	19'3" 5.87 M	6'10" 2.08 M	1300 LBS 590 KG	STANDARD STANDARD	20HP - 10KNOTS 40HP - 19KNOTS 60HP - 25KNOTS	SO TO	20-50 2x50	L L	60 70	22KNOTS	15KNOTS
FIVE 90^{TS}	19'3" 5.87 M	6'10" 2.08 M	1350 LBS 614 KG	STANDARD STANDARD	20HP - 10KNOTS 40HP - 19KNOTS 60HP - 25KNOTS	SO TO	20-50 2x50	L L	60 70	22KNOTS	15KNOTS
DAY ANGLER 19+	19'6" 5.95 M	7'6" 2.29 M	1650 LBS 750 KG	OPTIONAL STANDARD	30HP - 12KNOTS 50HP - 18KNOTS 65HP - 25KNOTS	SO TO SZ	30-60 2x35 50-80	L L	65 75 105	25KNOTS	15KNOTS
COMMERCIAL 21	21'0" 6.40 M	7'8" 2.32 M	1500 LBS 700 KG	OPTIONAL STANDARD	30HP - 12KNOTS 65HP - 22KNOTS 80HP - 25KNOTS	SO TO SZ	30-65 2x40 50-110	L L	80 100 125	25KNOTS	15KNOTS
DAY ANGLER 21	21'0" 6.40 M	7'8" 2.32 M	1870 LBS 850 KG	OPTIONAL STANDARD	30HP - 11KNOTS 65HP - 20KNOTS 80HP - 25KNOTS	SO TO SZ	30-65 2x40 50-110	L L	80 100 125	25KNOTS	15KNOTS
COMMERCIAL 23	23'0" 7.00 M	8'1" 2.50 M	1980 LBS 900 KG	OPTIONAL STANDARD	40HP - 12KNOTS 90HP - 22KNOTS 115HP - 24KNOTS	SO TO SZ	40-90 2x50 50-150	L L	115 120 150	24KNOTS	16KNOTS
DAY ANGLER 23	23'0" 7.00 M	8'1" 2.50 M	2310 LBS 1050 KG	OPTIONAL STANDARD	40HP - 12KNOTS 90HP - 22KNOTS 115HP - 24KNOTS	SO TO SZ	40-90 2x50 50-150	L L	115 120 150	24KNOTS	16KNOTS

Notes: 1. Weight of basic boat only. 2. Performance indicator based on one crew plus gear but otherwise light displacement. 3. SO=Single outboard engine TO=Twins outboard engines SZ=Single sterndrive 4. Tiller steer versions of performance and Day Angler models have reduced horse power ratings (consult your dealer or owners handbook) 5. Max speed in smooth water with light load. Boats should not be driven above the maximum design speed particularly in rough conditions.

Please note that performance indicators, where given, are approximate and not guaranteed. Lengths quoted do not include engines and other dimensions and data is for general guidance. Please ask your dealer for advice regarding suitability for your application particularly if it is unusual or arduous.

Orkney Boats Ltd, Ford Lane Industrial Estate,
Ford Lane, Yapton, Arundel, West Sussex BN18 0DF
Telephone: 01243 551456 Fax: 01243 551914

We are constantly seeking ways to improve our products and we therefore reserve the right to change specifications as necessary.
Some illustrations in this leaflet show boats fitted with optional equipment.
For full details of accessories, please see current price list.
Terms of business are available on request. E & OE

